

General Description

The ZMD68202

Ordering Information:
Absolute Maximum Ratings $T_C = 25$

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current	$I_{D@TC=25}$	9.0	A
	$I_{D@TC=75}$	7.0	A
	$I_{D@TC=100}$	5.6	A
Pulsed Drain Current	I_{DM}	13	A
Total Power Dissipation	$P_D@TC=25$	3.6	W
Total Power Dissipation	$P_D@TA=25$	0.69	W
Operating Junction Temperature	T_J	-55 to 150	
Storage Temperature	T_{STG}	-55 to 150	
Single Pulse Avalanche Energy	E_{AS}	30	mJ

Fig.1 Power Dissipation




Fig.2 Typical output Characteristics




Fig.3 Threshold Voltage V.S Junction Temperature



Fig.4 Resistance V.S Drain Current

Fig.7 Switching Time Measurement Circuit




Fig.8 Gate Charge Waveform




Fig.9 Switching Time Measurement Circuit




Fig.10 Gate Charge Waveform




Fig.11 Avalanche Measurement Circuit





Fig.12 Avalanche Waveform



Dimensions(SOP8)

Unit: mm

SYMBOL	min	TYP	max	SYMBOL	min		max
A	4.80		5.25	C	1.30		1.75
A1	0.37		0.49	C1	0.55		0.75
A2		1.27		C2	0.55		0.65
A3		0.41		C3	0.05		0.20
B	5.80		6.20	C4	0.10	0.20	0.23
B1	3.80		4.10	D		1.05	
B2		5.00		D1	0.40		0.62

